


Zitrox Compact

The Next Generation of Juicers



Zitrux Compact



Specifications

Fruit type	Oranges
Diameter of fruit	M Kit: 65-81 mm
Fruits per minute	40 fruits / min
Rate (juice / 250 ml)	1 juice in 5"
Tap operator	Touchless. No hand-tap contact. Actuation by positioning the bottle
Type of consumption	Very high
Feeder capacity	30 kg 66 lbs
Waste capacity	52 l
Bottle holder	38mm
Voltage	208-240 V 50/60 Hz
Power output	Squeezing 260 W 0.34 HP Cleaning with detergent 2300 W 3.08 HP
Consumption	Squeezing 1.2 A Cleaning with detergent 9.7 A

Installation specifications

Water Hardness	Between 5°fH y 8°fH (Soft Water)
Water inlet connection	G3/4 Female minium 12liters/ minute at a 2,5 bar (250 kPa)
Drain connection	Corrugated drain pipe Diameter 20mm

Technical Information

Safety	Double security detector in accesses to mobile elements. Motor locking detection
Sound pressure level	Below 70 dB
Connectivity	GSM & WIFI
Filling height	296 mm

Measurements

Measurements	631 x 736 x 1772 mm
Width Depth Height	24,8" x 28,9" x 69,7"
Net weight	183 Kg 403 lbs
Footprint	0,46 m²

Packaging

Dimensions package	880 x 810 x 2100 mm
Width Depth Height	34,6" x 31,9" x 82,6"
Package weight	209,5 kg 461,8 lb

Cleaning

Juice unit cleaning	Automatic
Juice unit rinsing	Automatic
Dosage of cleaning product	Automatic

Benefits:



Color:



Models:

